

STANDARD BATTEN SPACING:  
DECRA TILE: 14-1/2"  
DECRA SHAKE: 12-5/8"

DECRA ROOFING PANEL

FASTENERS:  
USE 8d CORROSION  
RESISTANT BOX NAILS OR  
MIN #9 CORROSION  
RESISTANT SCREWS  
(COLOR COORDINATED)

UNDERLAYMENT

SHEATHING: TYP  
MIN 15/32"

RAFTER

BATTENS:

2x2 NOMINAL WOOD OR STEEL  
HAT SECTIONS SUFFICIENT TO  
SPAN RAFTER SPACING.

WOOD BATTENS FASTENED TO  
DECK WITH 16d COMMON NAILS.

STEEL HAT SECTIONS FASTENED  
TO DECK WITH MIN #9x1-1/2"  
CORROSION RESISTANT SCREWS.

TITLE

Panel Installation and Batten Spacing - Tile and Shake

DRAWING No.

ARCH2003-1-01a

DECRA ROOFING SYSTEMS, INC.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF  
DECRA ROOFING SYSTEMS, INC. ANY REPRODUCTION IN PART OR IN WHOLE  
WITHOUT PRIOR APPROVAL AND WRITTEN PERMISSION IS PROHIBITED.

1230 RAILROAD ST. CORONA, CA 92882 PH (951)272-8180 Fax (951)272-4476

DATE: 03-29-13

SCALE: 2" = 1' 0"