



**FASTENERS:**  
 USE 8d CORROSION  
 RESISTANT BOX NAILS OR  
 MIN #9 CORROSION  
 RESISTANT SCREWS  
 (COLOR COORDINATED)

SIDE FLASHING

DECRA ROOFING PANEL:  
 BEND UP BACK EDGE 2"

1x4 BATTEN FOR  
 PANEL SUPPORT

RAFTER

SHEATHING: TYP  
 MIN 15/32"

UNDERLAYMENT

UNDERLAYMENT TO  
 TOP OF FLASHING

RAFTER

METAL FLUE

WOOD FRAMING

SIDE FLASHING

CHIMNEY SADDLE:  
 CONFORM TO FIT

DECRA ROOFING PANEL

**BATTENS:**  
 2x2 NOMINAL WOOD OR STEEL  
 HAT SECTIONS SUFFICIENT TO  
 SPAN RAFTER SPACING.  
 WOOD BATTENS FASTENED TO  
 DECK WITH 16d COMMON NAILS.  
 STEEL HAT SECTIONS FASTENED TO  
 DECK WITH MIN #9x1-1/2"  
 CORROSION RESISTANT SCREWS.

|  |   |
|--|---|
| <p>TITLE<br/> <b>Chimney- Wood framing- Siding - Tile and Shake</b></p>  | <p>DRAWING No.<br/> <b>ARCH2003-1-04c</b></p>   |
| <p><b>DECRA ROOFING SYSTEMS, INC.</b></p> <p>1230 RAILROAD ST. CORONA, CA 92882 PH (951)272-8180 Fax (951)272-4476</p> | <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF<br/> <b>DECRA ROOFING SYSTEMS, INC.</b> ANY REPRODUCTION IN PART OR IN WHOLE<br/>     WITHOUT PRIOR APPROVAL AND WRITTEN PERMISSION IS PROHIBITED.</p> <p>DATE: <b>03-29-13</b> SCALE: <b>2" = 1' 0"</b></p> |