

FASTENERS:  
 USE 8d CORROSION  
 RESISTANT BOX NAILS OR  
 MIN #9 CORROSION  
 RESISTANT SCREWS  
 (COLOR COORDINATED)

DECRA RIDGE VENT:  
 COMPRESS BETWEEN  
 PANEL BEND UP AND  
 HIP & RIDGE

DECRA TILE HIP & RIDGE

2x2 BATTENS:  
 STACK TO RAISE HIP &  
 RIDGE TO REQUIRED  
 HEIGHT

1" MIN OPENING  
 BETWEEN BOTTOM  
 OF HIP & RIDGE  
 AND TILE PAN

SHEATHING: CUT  
 1" GAP FROM  
 CENTER BEAM

UNDERLAYMENT

SHEATHING: TYP  
 MIN 15/32"

1x4 BATTEN FOR PANEL SUPPORT

DECRA TILE PANEL: BEND UP BACK EDGE 1-1/2"

RAFTER

TITLE  
**Ridge Vent Installation with Center Beam- Tile**

DRAWING No.  
**ARCH2003-1-09a1**

**DECRA ROOFING SYSTEMS, INC.**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF  
**DECRA ROOFING SYSTEMS, INC.** ANY REPRODUCTION IN PART OR IN WHOLE  
 WITHOUT PRIOR APPROVAL AND WRITTEN PERMISSION IS PROHIBITED.

1230 RAILROAD ST. CORONA, CA 92882 PH (951)272-8180 Fax (951)272-4476

DATE: **04-01-13**

SCALE: **3" = 1' 0"**