

FASTENERS:
 USE 8d CORROSION
 RESISTANT BOX NAILS OR
 MIN #9 CORROSION
 RESISTANT SCREWS
 (COLOR COORDINATED)

DECRA RIDGE VENT:
 COMPRESS BETWEEN
 PANEL BEND UP AND
 HIP & RIDGE

DECRA SHAKE HIP & RIDGE

2x2 BATTENS:
 STACK TO RAISE HIP &
 RIDGE TO REQUIRED
 HEIGHT

1" MIN OPENING
 BETWEEN BOTTOM
 OF HIP & RIDGE
 AND PANEL

SHEATHING: CUT
 1" GAP FROM
 CENTER BEAM

UNDERLAYMENT

DECRA SHAKE PANEL: BEND UP BACK EDGE 1-1/2"

SHEATHING: TYP
 MIN 15/32"

1x4 BATTEN FOR PANEL SUPPORT

RAFTER

TITLE
Ridge Vent Installation with Center Beam- Shake

DRAWING No.
ARCH2003-1-09b1

DECRA ROOFING SYSTEMS, INC.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
DECRA ROOFING SYSTEMS, INC. ANY REPRODUCTION IN PART OR IN WHOLE
 WITHOUT PRIOR APPROVAL AND WRITTEN PERMISSION IS PROHIBITED.

1230 RAILROAD ST. CORONA, CA 92882 PH (951)272-8180 Fax (951)272-4476

DATE: **04-01-13**

SCALE: **3" = 1' 0"**