



1x4 BATTEN:
RECOMMENDED
FOR ALIGNMENT
OF FIRST COURSE

DECRA VILLA TILE PANEL

FASTENERS:
USE MIN #9 CORROSION
RESISTANT SCREWS
(COLOR COORDINATED
IN EXPOSED AREAS)

VILLA BIRD STOP-EAVE

SHEATHING: TYP
MIN 15/32"

RAFTER

UNDERLAYMENT

1/4" MIN DROP
BETWEEN TOP EDGE
OF GUTTER AND
VILLA TILE PANEL

BARGE RAFTER

GUTTER:
GUTTER TO BE INSTALLED PRIOR TO BIRD STOP-EAVE
GUTTER SUPPORT BRACKETS RECOMMENDED OVER SPIKES

<p>TITLE Panel Installation Starter/Eave- Villa</p>	<p>DRAWING No. ARCH2007-4-01</p>
--	---

<p>DECRA ROOFING SYSTEMS, INC.</p>	<p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DECRA ROOFING SYSTEMS, INC. ANY REPRODUCTION IN PART OR IN WHOLE WITHOUT PRIOR APPROVAL AND WRITTEN PERMISSION IS PROHIBITED.</p>
---	---

<p>1230 RAILROAD ST. CORONA, CA 92882 PH (951)272-8180 Fax (951)272-4476</p>	<p>DATE: 05-10-13</p>	<p>SCALE: 3" = 1' 0"</p>
--	------------------------------	---------------------------------