




























MODELOS		ESPECIFICACIONES DEL PRODUCTO									
			DECRA VILLA TILE	DECRA TILE	DECRA SHINGLE XD®	DECRA SHAKE XD®	DECRA SHAKE				
DECRA VILLA TILE	DECRA TILE	Pendiente mínima ▶	14° (25%)	14° (25%)	19° (35%)	14° (25%)	14° (25%)				
		Dimensiones totales ▶	1124mm x 432mm	1321mm x 419mm	1330mm x 360mm	1324mm x 359mm	1346mm x 371mm				
DECRA SHINGLE XD	DECRA SHAKE XD	Exposición de la teja ▶	1003mm x 368mm	1270mm x 368mm	1260mm x 310mm	1267mm x 315mm	1295mm x 321mm				
	DECRA SHAKE	Tejas x M² ▶	2.72	2.15	2.55	2.51	2.42				
		Peso instalado ▶	8.1 kg / M².	7.3 kg / M².	7.3 kg / M².	7.3 kg / M².	7.3 kg / M².				
COLORES DISPONIBLES											
DECRA VILLA TILE											
	Amalfi Sand	Capri Clay	Pompeii Ash	Rustico Clay	Venetian Gold	Charcoal*	Woodland Green*	Antique Chestnut CC*	Mist Grey CC*	Tuscan Sun CC*	
DECRA TILE											
	Charcoal	Chestnut	Garnet	Terracotta	Weathered Timber	Granite Grey*	Shadowood*	Woodland Green*	Antique Chestnut CC*	Mist Grey CC*	Tuscan Sun CC*
DECRA SHINGLE XD											
	Classic Cobblestone	Midnight Eclipse	Natural Slate	Old Hickory	Woodland Green*	Antique Chestnut CC*	Mist Grey CC*	Tuscan Sun CC*			
DECRA SHAKE XD											
	Pinnacle Grey	Antique Chestnut	Midnight Eclipse*	Woodland Green*	Antique Chestnut CC*	Mist Grey CC*	Tuscan Sun CC*				
DECRA SHAKE											
	Charcoal	Chestnut	Granite Grey	Shadowood	Weathered Timber	Woodland Green*	Antique Chestnut CC*	Mist Grey CC*	Tuscan Sun CC*		

GARANTÍA/COMPOSICIÓN	
GARANTÍAS	
• Garantía Limitada De Por Vida* • Garantía De Vientos ≤ 120 mph (200 Km/h) • Garantía De Impacto Por Granizo	
COMPOSICIÓN	
• Acero calib. 26 & Aleación De Aluzinc • Primer De Base Acrílica • Adhesivo • Gránulos Recubiertos De Cerámica • Sellante Acrílico	
*DECRA ofrece una garantía limitada de por vida para viviendas unifamiliares en EE. UU. y Canadá.	

GARANTÍA/COMPOSICIÓN

GARANTÍAS

- Garantía Limitada De Por Vida*
- Garantía De Vientos ≤ 120 mph (200 Km/h)
- Garantía De Impacto Por Granizo

COMPOSICIÓN

- Acero calib. 26 & Aleación De Aluzinc
- Primer De Base Acrílica
- Adhesivo
- Gránulos Recubiertos De Cerámica
- Sellante Acrílico

*DECRA ofrece una garantía limitada de por vida para viviendas unifamiliares en EE. UU. y Canadá.

DECRA CUMPLE CON EVALUACIONES Y APROBACIONES DE:

International Code Council (IRC, IBC Codes)

INCLUDES: [City of Los Angeles \(LARC, LABC\)](#)

[California State \(CRC, CBC\)](#)

- [ESR-2901 – Tile, Shake, Shingle Plus \(battens\)](#)
- [ESR-1754 – Villa Tile, Shake XD, Shingle XD, Shingle Plus \(direct to deck\)](#)

Miami - Dade County, Florida

- [Miami Dade County NOA#18-1015.06 Tile, Villa Tile, Shake, Shingle Plus, Shake XD](#)
- [Miami Dade County NOA#17-1227.02 DECRA Ridge Vent](#)

Florida Building Code

- [Approval #9759-R9: Shake, Tile, Shingle XD, Shake XD, Villa Tile, Shingle Plus](#)
- [D30800.12.09-R7 for FL9759-R9](#)
- [DECRA Ridge Vent: FL17492-R3 II NOA 17122702 2017](#)

Texas Department of Insurance

- [Products Qualifying for Impact Resistant Roofing Credits](#)
- [Roofing Installation Information and Certification for Reduction in Residential Insurance Premiums](#)
- [TDI Report #RC-282 Wind Resistance – Villa Tile](#)

- [TDI Report #RC-235 Wind Resistance – Shake XD](#)
- [TDI Report #RC-281 Wind Resistance – Tile, Shake, Shingle Plus](#)
- [TDI Report #RC-548 Wind Resistance - Shingle XD](#)

Underwriters Laboratories, Inc – Listings File #R14710

- Fire – UL 790 (ASTM E108 – A, B & C)
- Fire – UL CAN/ULC-S107 (Canada)
- Hail – UL 2218 (Class 4)
- Uplift – UL 580 & UL 1897 – Class 90

Pruebas Adicionales para LEED® and CA Title 24 Cool Colors

- ASTM – E903 Solar Absorptance, Reflectance, and Transmittance of Materials Using Integrating Spheres
- ASTM – E408 Total Normal Emittance of Surfaces Using Inspection-Meter Techniques
- ASTM – E1980 Calculating Solar Reflectance Index of Horizontal and Low-Sloped Opaque Surfaces

ISO Management System Compliance

- [ISO 9001:2015 Quality Management System](#)
- [ISO 14001:2015 Environmental Management System](#)
- [ISO 45001:2018 Occupational Health & Safety Management System](#)

National Building Code of Canada

- [CCMC Evaluation Report #13551-R \(direct-to-deck\)](#)
- [CCMC Evaluation Report #10241-R \(on battens\)](#)

